

SeaRock XR7 Specs



L.D.A. HULL LENGTH 23' (6.99 M) BEAM 7' 8" (2.40 M) DRAFT 18.5" (0.47 M) WEIGHT OF HULL 3.500 LBS (1,550 KG) MAXIMUM LOAD CAT D (ENGINE+PERS+LUGGAGE) 2.866 LBS (1.300 KG) MAXIMUM LOAD CAT D (ENGINE+PERS+LUGGAGE) 2.866 LBS (1.300 KG) MAXIMUM ENGINE WEIGHT 200 HP (186 KW) / 300 HP (261 KW) MAXIMUM ENGINE WEIGHT 25" (0.63 M) FUEL CAPACITY 72 US GALLONS (270 L) WATER CAPACITY 23 US GALLONS (90 L) EE CERTIFICATION CAT. C 8 PER - CAT. D 10 PER BRIDGE CLEARANCE (T-TOP)				
HULL LENGTH 23' (6.99 M) BEAM 7' 8" (2.40 M) DRAFT 18.5" (0.47 M) WEIGHT OF HULL 3.500 LBS (1,550 KG) MAXIMUM LOAD CAT D (ENGINE+PERS+LUGGAGE) 2.866 LBS (1.300 KG) MIN / MAX HORSEPOWER 200 HP (186 KW) / 300 HP (261 KW) MAXIMUM ENGINE WEIGHT 910 LBS (413 KG) TRANSOM HEIGHT 25" (0.63 M) DEADRISE AT TRANSOM PUEL CAPACITY 72 US GALLONS (270 L) WATER CAPACITY 23 US GALLONS (90 L) CE CERTIFICATION	L.O.A.	5.41.11	(5.45)	
BEAM 7 8" (6.99 M) BEAM 7 8" (2.40 M) DRAFT 18.5" (1.47 M) WEIGHT OF HULL 3.500 LB (1,550 KG) MAXIMUM LOAD CAT D (ENGINE+PERS+LUGGAGE) 2.866 LB (1,550 KG) MIN / MAX HORSEPOWER 200 HP (186 KW) / 300 HP (261 KW) MAXIMUM ENGINE WEIGHT 910 LB (413 KG) TRANSOM HEIGHT 25" (1.63 M) DEADRISE AT TRANSOM FUEL CAPACITY 72 US GALLONS (270 L) WATER CAPACITY CE CERTIFICATION CAT. C 8 PER - CAT. U 10 PER		24′ ′′	(7.4U M)	
BEAM 7'8" (2.40 M) DRAFT 18.5" (0.47 M) WEIGHT OF HULL 3.500 LBS (1,550 KG) MAXIMUM LOAD CAT D (ENGINE+PERS+LUGGAGE) 2.866 LBS (1.300 KG) MIN / MAX HORSEPOWER 200 HP (186 KW) / 300 HP (261 KW) MAXIMUM ENGINE WEIGHT 910 LBS (413 KG) TRANSOM HEIGHT 25" (0.63 M) DEADRISE AT TRANSOM FUEL CAPACITY 72 US GALLONS (270 L) WATER CAPACITY 23 US GALLONS (90 L) CE CERTIFICATION CAT. C 8 PER - CAT. D 10 PER	HULL LENGTH			
7' 8" (2.40 M) DRAFT		23'	(6.99 м)	
DRAFT 18.5" 18.5" (0.47 M) WEIGHT OF HULL 3.500 LBS (1,550 KG) MAXIMUM LOAD CAT D (ENGINE+PERS+LUGGAGE) 2.866 LBS (1.300 KG) MIN / MAX HORSEPOWER 200 HP (186 KW) / 300 HP (261 KW) MAXIMUM ENGINE WEIGHT 910 LBS (413 KG) TRANSOM HEIGHT 25" (0.63 M) DEADRISE AT TRANSOM FUEL CAPACITY 72 US GALLONS WATER CAPACITY 23 US GALLONS (90 L) CE CERTIFICATION CAT. C 8 PER - CAT. D 10 PER	BEAM			
18.5" (0.47 M) WEIGHT OF HULL		7' 8"	(2.4□ M)	
18.5" (0.47 M)	DBAET			
WEIGHT OF HULL 3.500 LBS (1,550 KG) MAXIMUM LOAD CAT D (ENGINE+PERS+LUGGAGE) 2.866 LBS (1.300 KG) MIN / MAX HORSEPOWER 200 HP (186 KW) / 300 HP (261 KW) MAXIMUM ENGINE WEIGHT 910 LBS (413 KG) TRANSOM HEIGHT 25" (0.63 M) DEADRISE AT TRANSOM 20° FUEL CAPACITY 72 US GALLONS (270 L) WATER CAPACITY 23 US GALLONS (90 L) CE CERTIFICATION CAT. C 8 PER - CAT. D 10 PER	BRALL	10.5	(5.45)	
3.500 LBS (1,550 KG)		18.5"	(U.47 M)	
MAXIMUM LOAD CAT D (ENGINE+PERS+LUGGAGE) 2.866 LBS (1.300 KG) MIN / MAX HORSEPOWER 200 HP (186 KW) / 300 HP (261 KW) MAXIMUM ENGINE WEIGHT 910 LBS (413 KG) TRANSOM HEIGHT 25" (0.63 M) DEADRISE AT TRANSOM 20° FUEL CAPACITY 72 US GALLONS (270 L) WATER CAPACITY 23 US GALLONS (90 L) CE CERTIFICATION CAT. C 8 PER - CAT. D 10 PER	WEIGHT OF HULL			
## 2.866 LBS (1.300 KG) MIN / MAX HORSEPOWER 200 HP (186 KW) / 300 HP (261 KW) MAXIMUM ENGINE WEIGHT 910 LBS (413 KG) TRANSOM HEIGHT 25" (0.63 M) DEADRISE AT TRANSOM 20° FUEL CAPACITY 72 US GALLONS (270 L) WATER CAPACITY 23 US GALLONS (90 L) CE CERTIFICATION CAT. C 8 PER - CAT. D 10 PER		3.500 LBS	(1,550 KG)	
MIN / MAX HORSEPOWER 200 HP (186 KW) / 300 HP (261 KW) MAXIMUM ENGINE WEIGHT 910 LBS (413 KG) TRANSOM HEIGHT 25" (0.63 M) DEADRISE AT TRANSOM FUEL CAPACITY 72 US GALLONS (270 L) WATER CAPACITY 23 US GALLONS (90 L) CE CERTIFICATION CAT. C 8 PER - CAT. D 10 PER	MAXIMUM LOAD CAT D (ENGINE+PERS+LUGGAGE)			
MIN / MAX HORSEPOWER 200 HP (186 KW) / 300 HP (261 KW) MAXIMUM ENGINE WEIGHT 910 LBS (413 KG) TRANSOM HEIGHT 25" (0.63 M) DEADRISE AT TRANSOM FUEL CAPACITY 72 US GALLONS (270 L) WATER CAPACITY 23 US GALLONS (90 L) CE CERTIFICATION CAT. C 8 PER - CAT. D 10 PER		2 866 185	(1 300 Kg)	
200 HP (186 KW) / 300 HP (261 KW) MAXIMUM ENGINE WEIGHT 910 LBS (413 KG) TRANSOM HEIGHT 25" (0.63 M) DEADRISE AT TRANSOM 20° FUEL CAPACITY 72 US GALLONS (270 L) WATER CAPACITY 23 US GALLONS (90 L) CE CERTIFICATION CAT. C 8 PER - CAT. D 10 PER	MINI / MAY HODGEDOWED	2.000 2.55	(11000 Re)	
MAXIMUM ENGINE WEIGHT 910 LBS (413 KG) TRANSOM HEIGHT 25" (0.63 M) DEADRISE AT TRANSOM 20° FUEL CAPACITY 72 US GALLONS (270 L) WATER CAPACITY 23 US GALLONS (90 L) CE CERTIFICATION CAT. C 8 PER - CAT. D 10 PER	MIN / MAX HURSEPUWER			
910 LBS (413 KG) TRANSOM HEIGHT 25" (0.63 M) DEADRISE AT TRANSOM 20° FUEL CAPACITY 72 US GALLONS (270 L) WATER CAPACITY 23 US GALLONS (90 L) CE CERTIFICATION CAT. C 8 PER - CAT. D 10 PER		200 нр (186 кW) /	300 HP (261 KW)	
TRANSOM HEIGHT 25" (O.63 M) DEADRISE AT TRANSOM 20° FUEL CAPACITY 72 US GALLONS (270 L) WATER CAPACITY 23 US GALLONS (90 L) CE CERTIFICATION CAT. C 8 PER - CAT. D 10 PER	MAXIMUM ENGINE WEIGHT			
TRANSOM HEIGHT 25" (O.63 M) DEADRISE AT TRANSOM 20° FUEL CAPACITY 72 US GALLONS (270 L) WATER CAPACITY 23 US GALLONS (90 L) CE CERTIFICATION CAT. C 8 PER - CAT. D 10 PER		910 LBS	(413 KG)	
DEADRISE AT TRANSOM 20° FUEL CAPACITY 72 US GALLONS (270 L) WATER CAPACITY 23 US GALLONS (90 L) CE CERTIFICATION CAT. C 8 PER - CAT. D 10 PER	TRANSOM HEIGHT	<u> </u>	(1 1 2 1 1 2)	
DEADRISE AT TRANSOM 20° FUEL CAPACITY 72 US GALLONS (270 L) WATER CAPACITY 23 US GALLONS (90 L) CE CERTIFICATION CAT. C 8 PER - CAT. D 10 PER	TRANSOM REIGHT		.	
FUEL CAPACITY 72 US GALLONS (270 L) WATER CAPACITY 23 US GALLONS (90 L) CE CERTIFICATION CAT. C 8 PER - CAT. D 10 PER		25"	(П.63 М)	
FUEL CAPACITY 72 US GALLONS (270 L) WATER CAPACITY 23 US GALLONS (90 L) CE CERTIFICATION CAT. C 8 PER - CAT. D 10 PER	DEADRISE AT TRANSOM			
72 US GALLONS (270 L) WATER CAPACITY 23 US GALLONS (90 L) CE CERTIFICATION CAT. C 8 PER - CAT. D 10 PER			20°	
72 US GALLONS (270 L) WATER CAPACITY 23 US GALLONS (90 L) CE CERTIFICATION CAT. C 8 PER - CAT. D 10 PER	FUEL CAPACITY			
WATER CAPACITY 23 US GALLONS (90 L) CE CERTIFICATION CAT. C 8 PER - CAT. D 10 PER	TOLL OAT ADIT!	77 115 0411 0410	(270.1)	
23 US GALLONS (90 L) CE CERTIFICATION CAT. C 8 PER - CAT. D 10 PER		/Z US GALLUNS	(Z/U L)	
CE CERTIFICATION CAT. C 8 PER - CAT. D 10 PER	WATER CAPACITY			
CAT. C 8 PER - CAT. D 10 PER		23 US GALLONS	(90 L)	
	CE CERTIFICATION			
		CAT. C 8 PER - CAT. D 10 PER		
BRIDGE GLEARANGE (I-TUP) 8' (2.45M)	BRIDGE BLEADANGE (TT)			
	BRIDGE GLEARANGE (1-10P)	6 ['] (2.45	MI)	

STANDARD EQUIPMENT

DECK

6 CLEATS

STAINLESS STEEL SWIM LADDER

STAINLESS STEEL ANCHOR ROLLER WITH CLEAT

PILOT AND CO-PILOT SEATS

AFT AND FORWARD BENCH WITH CUSHION

CONSOLE AND ELECTRICAL

WINDSHIELD

HI QUALITY STEERING WHEEL

RITCHIE COMPASS

ELECTRONICS MOUNTING SURFACE

INSTRUMENTATION AND ELECTRICAL SWITCH PANEL WITH

CIRCUIT BREAKER PROTECTION

FUEL GAUGES

SIDE CONSOLE HAND RAILS

ENGINE BATTERY, 1 X 100 AH

SERVICE BATTERY, 1 X 100 AH

NAVIGATION LIGHT

Horn

BLOWER

PLASTIC WATER TANK WITH PUMP AND SHOWER

STORAGE

BOW ANCHOR LOCKER WITH DRAIN

FRONT CONSOLE STORAGE + 6 WIDE STORAGE SPACE

LIFERAFT STORAGE AREA

MECHANICAL

HYDRAULIC STEERING

ELECTRICAL BILGE PUMPS

PLASTIC FIXED FUEL TANK 300 LT WITH DECK FILLERS

ACCESSORIES

ELECTRICAL WINDLASS & REMOTE 700W

ANCHORING KIT - GALVANIZED ANCHOR & CHAIN

MODRING KIT - 4 x 7 M 12MM ROPES FOR DOCKING, 6 FENDERS

REMOVABLE REFRIGERATOR

ALU T-TOP WITH LIFEBUOY STORAGE

ROLL BAR WITH TENT

EVA COCKPIT FLOOR & SWIM PLATFORM

FOREDECK ADJUSTABLE HDPE TABLE WITH CONVERSION TO SUNBED

LIFT KIT

NON-OXYGENATED LIVEWELL

ROD HOLDERS ON SIDE DECKS - 4

TACKLE BOX STORAGES

SEARCH LIGHT

CHARTPLOTTER

TRANSDUCER

FISHFINDER

VHF

MARINE STEREO SOUND SYSTEM

COVERS

ALL SEAROCK MODELS ARE FULLY CUSTOMIZABLE ACCORDING TO THE REQUESTS OF THE MOST DEMANDING OWNERS.

NOTICE: CUSTOMS DUTIES, TRANSPORT, CRANE COSTS & BOAT LAUNCH PREPARATIONS ARE NOT INCLUDED.

SEAROCK BOATS RESERVES THE RIGHT TO CHANGE THE PRICES AND THE EQUIPMENT WITHOUT PRIOR INFORMATION, AS WELL AS THE TECHNICAL DATA.

ALL TAXES, CUSTOMS, MARINA AND ETC COSTS ARE CUSTOMERS' RESPONSIBILITY. ALL RIGHTS RESERVED.

THIS TECHNOLOGY IS PATENT-PROTECTED